

HTML Attributes

commandfor: <element-id>

Target element to invoke (no #)

command: <action>

Action to perform on target

Built-in Commands

Dialog

show-modal

close

request-close

Popover

toggle-popover

show-popover

hide-popover

Dialog commands: close vs request-close

close closes immediately

request-close fires a `cancel` event on dialog. `preventDefault()` on this event to prevent close

Dialog closedby Attribute

closedby: any closerequest none

How dialog is dismissed

any light dismiss + Esc

closerequest Esc only

none explicit close only

Custom Commands

command: --custom-name

Dispatch a `CommandEvent` on the target.

Tooltips

interestfor: <element-id>

Popover target to show on hover.

Dialog Example

```
<button commandfor="dlg"
        command="show-modal">
```

Open

```
</button>
```

```
<dialog id="dlg" closedby="any">
  <button commandfor="dlg"
    command="request-close">×</button>
</dialog>
```

```
dlg.addEventListener('cancel',
(e) => {
  if (!canClose) e.preventDefault();
});
```

Popover Example

```
<button commandfor="menu"
        command="toggle-popover">
```

Menu

```
</button>
```

```
<div id="menu" popover>
  Content
</div>
```

Custom Command

```
<button commandfor="vid"
        command="--play">Play</button>
```

```
vid.addEventListener('command',
(e) => {
  if (e.command === '--play')
    vid.play();
});
```